TY524MX 1/3



PRODUCT-DETAILS

TY524MX

CBL TIE 30LB 5.5 UV BLACK 2-PC DIS



| General Information | |
|-----------------------|--|
| Extended Product Type | TY524MX |
| Product ID | 7TAG009090R0007 |
| EAN | 5414363065531 |
| Catalog Description | CBL TIE 30LB 5.5 UV BLACK 2-PC DIS |
| Long Description | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 137mm (5.4 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 178 Newtons (40 Pounds) |

| Ordering | |
|-------------------------|--------------------|
| EAN | 5414363065531 |
| UPC | 786210806990 |
| Country of Origin | United States (US) |
| Selling Unit of Measure | each |

Dimensions

TY524MX 2/3

| Product Net Width | 0.14 in |
|---------------------|---------|
| | 3.6 mm |
| Product Net Depth / | 5.4 in |
| Length | 137 mm |

| Container Information | |
|-----------------------------------|----------------------|
| Package Level 1 Units | 100 EA |
| Package Level 1 Width | 127 mm 5 in |
| Package Level 1 Height | 0 mm 0 in |
| Package Level 1 Depth / Length | 266.7 mm 10.5 in |
| Package Level 2 Units | 1000 EA |
| Package Level 2 Width | 101.6 mm 4 in |
| Package Level 2 Height | 160.02 mm 6.3 in |
| Package Level 2 Depth / Length | 241.3 mm 9.5 in |
| Package Level 3 Units | 363000 EA |
| Package Level 3 Width | 0.025 mm 0.001 in |
| Package Level 3 Height | 0.025 mm 0.001 in |
| Package Level 3 Depth / Length | 0.025 mm 0.001 in |

Environmental

| 5/863 July 22, 2019 |
|---------------------|
| L |

| Additional Information | |
|------------------------|--|
| Brand / Label | Ty-Rap |
| Bundle Diameter | 0.08 to 1.38 in 2 to 35 mm |
| Color | Black |
| Effective Date | 19730723 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Product Name | Other |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Tensile Strength | 40 lb 178 N |
| Thickness | 0.04 in 1.0 mm |

Certificates and Declarations

Data Sheet, Technical TDS000566 Information

TY524MX 3/3

Declaration of 9AKK107492A9841 Conformity - CE

| Classifications | |
|---------------------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

