

ICCONS® Hollow Wall Anchor

- Carbon Steel, Zinc Galvanised Clear



- All metal construction
- Anti-rotation barbs, incorporated in the flange, prevent anchor rotation
- Flush Finish Head
- Oversized Flanged Head prevents head pull in on delicate substrates
- Once installed screw can be completely removed allowing fixture fitting

		ICCONS® Hollow Wall Anchor Product Code						
		HA4XS	HA4S	HA4SL	HA4L	HA6S	HA8S	
Nominal Drill Diameter	Screw diameter	8mm	8mm	8mm	8mm	10mm	11mm	
	Recommended Panel Thickness	0-5 mm	5-10 mm	10-18 mm	18-24 mm	10-21 mm	10-21 mm	
Additional Technical Information								
	Anchor Diameter	7mm	7mm	7mm	7mm	9mm	10mm	
	Anchor Length	20mm	32mm	46mm	46mm	52mm	52mm	
	Anchor Neck Length	3mm	6mm	10mm	20mm	12mm	10mm	
	Anchor Flange OD	14mm	14mm	14mm	14mm	16mm	18mm	
	Screw Head OD	8mm	8mm	8mm	8mm	10mm	11.5mm	
	Washer OD	9.5mm	9.5mm	9.5mm	9.5mm	12.5mm	12.5mm	
	Screw Length	28mm	41mm	54mm	54mm	60mm	60mm	
		Recommended Loads (W.L.L.)						
		M4 Tension	M4 Shear	M6 Tension	M6 Shear	M8 Tension	M8 Shear	
		10mm Gypsum Board	20kg	50kg	20kg	50kg	20kg	50kg
		13mm Gypsum Board	20kg	50kg	20kg	50kg	20kg	50kg

ICCONS Pty Ltd.

Head Office, 12-18 Produce Drive,
Dandenong South, Victoria, 3175

P: 03 9706 4344
F: 03 9768 3329
E: info@iccons.com.au

