Technical Bulletin



ICCONS® Spring Toggles

- Zinc Clear



- All Metal Construction
- Wide Wingspan
- Secure Through-fix
- Cup Hook Version Available
- Multiple Fixture Thickness
- Clean, low profile aesthetic appearance

All metal construction Spring Toggle Anchors are, ideal for both wall and ceiling applications. Wide wingspan provides high loadings in plasterboard and other cavity applications.

Performance Information

Allowable Working Load (W.L.L.) 10mm Plasterboard				
Part No.		Description	Fixture Thickness	Tensile Capacity
STR18-2		1/8" x 50mm Round Head	30mm	8 kg
STR18-3		1/8" x 75mm Round Head	50mm	8 kg
STR316-2		3/16" x 50mm Round Head	25mm	10 kg
STR316-3		3/16" x 75mm Round Head	48mm	10kg
	STRCH316-3	3/16" x 75mm Cup Hook	50mm	10kg
STR316-4		3/16" x 100mm Round Head	74mm	10kg

Note: The above information is representative of a single anchor installed in a 10mm plasterboard cavity wall. Capacities listed above are allowable working loads and incorporate a factor of safety ≥3

ICCONS Pty Ltd.

Head Office, 12-18 Produce Drive, Dandenong South, Victoria, 3175

riulsider











P: 03 9706 4344

F: 03 9768 3329

E: info@iccons.com.au

Technical Bulletin

ICCONS Pty Ltd.

Head Office, 12-18 Produce Drive, Dandenong South, Victoria, 3175













P: 03 9706 4344

F: 03 9768 3329 E: info@iccons.com.au