

PRODUCT DATASHEET

LED Value Weatherproof Batten 1500 25/50W TRI IP65

LEDVALUE IP65 POWER AND CCT CHANGE WEATHERPROOF BATTEN | Weatherproof batten family with high IP rating and CCT and power change



Areas of application

- Car parks and underpasses
- Garages
- Industrial and storage facilities

Product benefits

- Homogeneous light output
- High-power LED for high light output

Product features

- Average lifespan: 50,000 h
- Type of protection: IP65
- 6 mm terminal block for easy installation



TECHNICAL DATA

Electrical data

Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	0.90
Total harmonic distortion	< 25 %
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous efficacy	100 lm/W
Color rendering index Ra	80
Standard deviation of color matching	6 sdcn
Beam angle	111 °

Dimensions & Weight

Length	1500.00 mm
Width	96.00 mm
Height	79.00 mm
Product weight	1950.00 g

Materials & Colors

Product color	Blue/gray
Housing color	Blue/gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting





Type of connection	Terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling

LED module replaceable	Not replaceable
------------------------	-----------------

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	100000

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	User instruction
	Tender documents
	IES file (IES)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075393578	Folding box 1	1,505 mm x 100 mm x 83 mm	2209.00 g	12.49 dm ³
4058075393585	Shipping box 6	1,519 mm x 178 mm x 244 mm	14309.00 g	65.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

