

SabreFix™ PS

SabreFix PS is a premium grade, solvent-based panel construction adhesive, that is fast-drying and builds up strength quickly on contact. SabreFix PS is suitable for use on most common construction materials and is safe for use on polystyrene panels. Ideal for fixing wallboards, polystyrene panels, and acrylic shower linings.

Substrates

- Aluminium
- Cement sheet
- Concrete
- Mirror backing
- Plasterboard
- Steel
- Timber – including LOSP treated timber
- Most construction substrates

Surface Preparation

Ensure all surfaces are clean and dry. Free from all loose paint, dust, grease and release agents.



Features

- Interior/Exterior
- Easy gunning
- High bond strength
- Fast curing – Flexible
- Bonds to most surfaces*
- Meets AS2329 Mastic adhesives for fixing wallboards

Application

General Application – Low Stress Loading. Cut the tip of the nozzle at a 45° angle to give a 5mm bead. Open cartridge, attach nozzle and place into a caulking gun. Apply a continuous bead of adhesive every 300 to 400mm along the fixing surface. Immediately press the two surfaces together to ensure good surface wetting. Prop if necessary and allow to dry for 2 to 4 hours before removing prop.

Polystyrene Application. Apply as above, but after ensuring good surface wetting, the materials

should be separated for up to 5 minutes to allow most of the solvent to escape. The surfaces are then pressed back together for final bond.

Heavy Materials – High Stress Loading. Apply a 4mm bead along all mating surfaces (total coverage) and immediately bring the two surfaces together. Nail the surfaces around the perimeter, sufficient to hold the two materials together for a minimum of eight hours. Remove the nails if required after the bond has gained sufficient strength.

Specification

Type	Synthetic rubber/resin mastic
Colour	Brown
Viscosity	Medium non slump paste.
Application temperature	5 to 40°C
Specific Gravity	1.14
Open time	20 minutes
Coverage	Approximately 20 metres on a 5mm bead per 375ml cartridge.
Specification	Meets AS 2329 Mastic Adhesives for fixing Wallboards.
Cleaner	Polystyrene: Hexane
Other applications	Mineral turpentine

Dried product is best removed by scraping or sanding.

Limitations

- Will not bond polyethylene or Teflon
- At least one substrate surface should be permeable material such as wood, cement or plasterboard. This allows the adhesive to reach full cure by solvent release over several days. If both substrates are impermeable materials such a metal, full bond strength development may be quite slow.
- Not recommended for vinyl or substrates that will be covered with vinyl wallpaper.
- If SabreFix PS is being used on a previously untested surface, carry out a trial or ask Maxilam first.
- Do not bond to painted or coated surfaces as the solvent in the product may weaken the coating.
- In applications directly exposed to weathering SabreFix PU 30 min is recommended. CLEANING mineral turpentine while adhesive is wet. Use Sabre Wipes to remove adhesive from skin. Dried adhesive is best removed by scraping or sanding

Cleaning

Mineral turpentine while adhesive is wet. Use Sabre Wipes towels remove adhesive from skin. Dried adhesive is best removed by scraping or sanding.

Storage & Shelf Life

Store in a cool dry place below 25°C and out of direct sunlight. Shelf life is 12 months from the date of manufacture when stored as directed.

Directions For Use

Read and understand the Material Safety Data Sheet before using this product.

Disposal

Empty cartridges may be disposed via local landfill. If spilt, absorb with clay, sand or earth. Collect and seal in properly labelled metal container. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

Precautions in Use

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Maxilam products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit www.maxilam.co.nz for copies. **HIGHLY FLAMMABLE – KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME KEEP OUT OF REACH OF CHILDREN KEEP CLOSED WHEN NOT IN USE** **FIRST AID** Swallowed: Do not induce vomiting, give a glass of water and contact a doctor immediately. Skin: Remove contaminated clothing, wash with warm soapy water. Do not scrub. Inhaled: Remove person to fresh air. Get medical advice if breathing becomes difficult. If inhaled to excess, remove from contaminated area – apply artificial respiration if not breathing. Eyes: Hold open and flood with water for at least 15 minutes. Get medical advice. For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMICALL, phone 0800 243 622.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

New Zealand

+64 6 366 0007
40-42 Cambridge St South
Levin 5510

Melbourne

+61 3 8657 5507
67 Gateway Blvd
Epping, VIC 3076

Sydney

+61 2 9098 8244
Level 6, 10 Herb Elliott Ave
Sydney Olympic Park, NSW 2127