

Exit LED Quickfit®

Exit LED Quickfit weatherproof remote



Range

Non-standard range

Product group

Exit LED Quickfit®

Features

- 3 year warranty
- Used in combination with remote power supply; exit mounted inside the freezer or coolroom and remote power supply mounted outside up to 10m away from the exit
- LED technology 100,000 hours lamp life
- IP65 weatherproof enclosure
- Quickfit® unique steel slide connect bracket for quick installation and easy maintenance
- UV stabilised vandal resistant polycarbonate cover
- Increased safety and no shock hazard by isolating the AC primary circuits from the unit
- Ideal for freezer or coolroom applications up to -30°C
- Includes all pictograph diffuser options for single and double sided installation
- Can be wall or ceiling mounted and optional bracket kits available for strengthened wall and cantilever mounting
- Remote power supply available in standard, Nexus® LX and Nexus RF configurations. Refer to separate technical data sheets; PSLED1W6, PSNXSLED1W6, PSNRFLED1W6, WPPSLED1W6, WPPSNXSLED1W6, WPPSNRFLED1W6



Standard products

Catalogue no.	Description
PWQFFRLEDP	LED Quickfit weatherproof remote exit

Accessories

Catalogue no.	Description
03-02061	Ceiling bracket assembly
WQFCLH	Cantilever mounting bracket - heavy duty
WQFCLL	Cantilever mounting bracket - light duty
WQFWM	Wall mount bracket

Dimensions

Length	Width	Height
466mm	155mm	274mm

Construction

Part	Construction
Body	Black UV/FR polycarbonate
Diffuser	Opal acrylic
Bracket	Black powder coated zinc steel
Enclosure cover	UV polycarbonate
Enclosure base	Black glass reinforced UV stabilised nylon

Light source

Model	Light source
Standard	Multiple LED 1.6W

Power consumption

Model	Power consumption
Standard/Nexus LX/ Nexus RF	See separate technical data sheets; PSLED1W6, PSNXSLED1W6, PSNRFLED1W6, WPPSLED1W6, WPPSNXSLED1W6, WPPSNRFLED1W6

Photometrics

Model	Class	Classification
Standard	C0	D3.2
	C90	D3.2

Note: Designed to comply with AS2293 and meet relevant Australian EMC standards

For more information please contact:

ABB Australia Pty Limited

Phone: 1300 666 595

Fax: 1300 666 594

E-mail: AU-ABB-Stanilite@abb.com

www.stanilite.com.au

Note: We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilisation of its contents – in whole or in parts – is forbidden without prior written consent of ABB.

Copyright © 2016 ABB
All rights reserved