

Motion detector

IS 3360 MX Highbay

EAN 4007841033569



Functional description

The ceilings are generally quite high in industrial halls and business premises. Good to know then that even high ceilings do not present a problem to the IS 3360 MX Highbay. The long-reach motion detector has an extra-large detection zone and remains absolutely alert even when it is installed at a height of up to 14 metres. The IS 3360 MX Highbay is highly reliable.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	65 x 95 x 95 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Type of installation	Surface wiring
Switching zones	1416 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	Ø 36 m (1018 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	5 s – 15 min
Switching output 1, resistive	2000 W
Switching output 1, number of LEDs / fluorescent lamps	8 stk.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Sensor	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	COM1 - surface-mounted installation, square