

Motion detector

IS 2360 DE ECO

EAN 4007841034733



Function description

Intelligent technology for installation. Infrared wall sensor IS 2360 DE ECO, for indoors and out, ideal for installing in projecting roofs and suspended ceilings, 360° angle of coverage, reach can be set up to 4 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

Technical specifications

Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	outdoors, Indoors
Installation site	ceiling
Type of installation	Installation
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,20 – 4,00 m
Optimum mounting height	2,5 m
Detection angle	360 °
Angle of aperture	180 °
Capability of masking out individual segments	Yes
Reach, radial	Ø 4 m (13 m ²)
Reach, tangential	Ø 8 m (50 m ²)
Twilight setting	2 – 2000 lx
Time setting	8 sec – 35 min
Switching output 1, number of LEDs / fluorescent lamps	6 pcs.

Motion detector

IS 2360 DE ECO

EAN 4007841034733

Technical specifications

Constant-lighting control	No
Settings via	Potentiometers
Type of interconnection	Master/master
IP rating	IP54
Ambient temperature	-20 – 40 °C
Colour	white
Colour, RAL	9010
IDs, certificates	VDE
Manufacturer's Warranty	5 years
PU1, EAN	4007841034733