

## tesa® 60804 PVC Electrical Tape

Plasticised PVC Black, Red, White, Blue Green, Yellow, Yellow/Green

### Main Application

- Used to electrically insulate joints and splices in wire and cables

### Technical Data

▪ Backing material	PVC film	▪ Elongation at break	200 %
▪ Total thickness	150 µm	▪ Tensile strength	28.4 N/cm
▪ Adhesion to steel	2 N/cm	▪ Dielectric breakdown voltage	1250 volt
▪ Temperature Min/Max		▪ Rated Operational temp	-40 to +80 C



For latest information on this product please visit <http://l.tesa.com/?ip=60804>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



**tesa tape Australia Pty. Ltd**  
Unit 8, 4 Southridge St  
Eastern Creek NSW 2766  
Tel 1800 226 851  
Fax +61 2 9830 3928  
[www.tesa.com](http://www.tesa.com)

## Performance Statement

**Producer:** tesa Australia & New Zealand

**Product:** 60804 / 60805

tesa tape Australia Pty Ltd hereby confirm that tesa 60804 and 60805 PVC Electrical Tapes are free from lead.

Date: 30/06/2020

Signature

A handwritten signature in black ink, appearing to read "Rohan Waugh". The signature is stylized and cursive.

Rohan Waugh  
National Sales & Marketing Manager