

## tesa® 4050

### Plasticised PVC Joining Tape

Highly conformable backing has good impact and abrasion resistance. Aggressive adhesive holds well on a wide variety of surfaces.

### Main Application

Joining poly-sheeting used in the building industry.  
Sealing pre-fabricated formwork.

### Technical Data

|                     |              |                               |         |
|---------------------|--------------|-------------------------------|---------|
| ▪ Backing material  | soft PVC     | ▪ Elongation at break         | 200 %   |
| ▪ Total thickness   | 130 µm       | ▪ Tensile strength            | 19 N/cm |
| ▪ Type of adhesive  | rubber based | ▪ Temperature resistance max. | 80 °C   |
| ▪ Adhesion to steel | 1.5 N/cm     |                               |         |

### Additional Information

Available in the colours silver and black.



For latest information on this product please visit <http://l.tesa.com/?ip=04050>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.