



 PRODUCT-DETAILS

TY5253MX

CABLE TIE 50LB 11 UV BLK 2-PC DIST



General Information

| | |
|-----------------------|--|
| Extended Product Type | TY5253MX |
| Product ID | 7TAG009180R0007 |
| EAN | 5414363065593 |
| Catalog Description | CABLE TIE 50LB 11 UV BLK 2-PC DIST |
| Long Description | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (222 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 289.7mm (11.40 Inches), Width of 4.82mm (0.19 Inches), Thickness of 1.3mm (0.05 Inches). Tensile Strength Rating of 222 Newtons (50 Pounds) |

Ordering

| | |
|-------------------------|--------------------|
| EAN | 5414363065593 |
| UPC | 786210885131 |
| Country of Origin | United States (US) |
| Selling Unit of Measure | each |

Dimensions

| | |
|-------------------|---------|
| Product Net Width | 0.19 in |
|-------------------|---------|

| | |
|----------------------------|-------------------|
| | 4.9 mm |
| Product Net Depth / Length | 11.6 in 295 mm |

Container Information

| | |
|--------------------------------|-----------------------|
| Package Level 1 Units | 100 EA |
| Package Level 1 Width | 0 mm 0 in |
| Package Level 1 Height | 0 mm 0 in |
| Package Level 1 Depth / Length | 0 mm 0 in |
| Package Level 2 Units | 500 EA |
| Package Level 2 Width | 133.35 mm 5.25 in |
| Package Level 2 Height | 139.7 mm 5.5 in |
| Package Level 2 Depth / Length | 387.35 mm 15.25 in |
| Package Level 3 Units | 96000 EA |
| Package Level 3 Width | 0 mm 0 in |
| Package Level 3 Height | 0 mm 0 in |
| Package Level 3 Depth / Length | 0 mm 0 in |

Technical UL/CSA

| | |
|--------------------------------|-----|
| Flammability According to UL94 | V-2 |
|--------------------------------|-----|

Additional Information

| | |
|-------------------|--|
| Brand / Label | Ty-Rap |
| Bundle Diameter | 0.12 to 3.07 in 3 to 78 mm |
| Color | Black |
| Effective Date | 19720620 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Product Name | Other: Other |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Tensile Strength | 50 lb 222 N |
| Thickness | 0.05 in 1.3 mm |

Certificates and Declarations

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000518 |
| Declaration of Conformity - CE | 9AKK107492A9841 |

Classifications

| | |
|------------------------------------|---------------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

